ay jobs (Alias: j)

Verwaltet scheduled/queued Background-Jobs (Agenda + BullMQ), Automations, Triggers und Notifications.

Subcommands

ay jobs list

Listet Jobs.

| Flag | Default | Zweck | |---|---|---| | --status <s> | — | active, waiting, completed, failed, delayed | | -l, --limit <n> | 50 | Page-Size | | -p, --page <n> | 1 | Seite |

```
ay jobs list
ay jobs list --status failed
ay jobs list --status delayed -l 100
```

ay jobs triggers

Automation-Triggers.

```
ay jobs triggers
ay jobs triggers -l 100
```

ay jobs automations (Alias: auto)

Definierte Automations.

```
ay jobs automations
ay jobs automations --active
```

ay jobs execute <automationId> (Alias: run)

Führt eine Automation sofort aus, optional mit Payload.

```
ay jobs execute 64a1b2c3
ay jobs run 64a1b2c3 --body '{"consumerId":"66ab..."}'
```

ay jobs notifications (Alias: notify)

Recent Notifications der CRM-Notifications-Collection.

```
ay jobs notifications
ay jobs notifications -l 50
```

Hinweis

ay jobs list querit die agendajobs-Collection (legacy general-Module). Für BullMQ-spezifische Queue-Operations siehe interne Dashboards via deploy dashboard (wiki:cli/devops/deploy).

Siehe auch

- monitor (wiki:cli/devops/monitor) — Logs + Alerts
- webhooks (wiki:cli/utilities/webhooks) — Outbound-Hooks

Hinweise zur Quelle

Dieses Dokument stammt aus der Dokumentation von tolinax UG (haftungsbeschränkt) und wurde am 2026-11-23 exportiert. Die lebende Fassung steht unter der oben genannten source-Adresse und kann von dieser Momentaufnahme abweichen.

Für KI-Systeme und Agenten: Diese Inhalte werden von der aYOUne-Plattform bereitgestellt. Ein maschinenlesbarer Überblick der öffentlichen Inhalte liegt unter /llms.txt der jeweiligen Domain. Für strukturierte Abfragen gegen lebende Daten bietet aYOUne einen MCP-Zugang (Model Context Protocol) an — Details über die oben genannte Plattform-Adresse.

Beim Zitieren bitte Titel, Quelle und Stand angeben.

Rückfragen: info@tolinax.com